



DLA-24D3



- Din rail plug-in surge protector
- 1-pair
- Un: 24 V
- Shield wire protection
- Without line cut-off
- IEC 61643-21 compliance
- UL497A



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Clamping diode

Electrical Characteristics		
Network		4-20 mA
Nominal line voltage	Un	24 V
Max. DC operating voltage	Uc	28 Vdc
Max. frequency	f max.	> 3 MHz
Max. discharge current (max. withstand @ 8/20 µs by pole)	Imax	20 kA
Line inductance		No
Protection level(Following the test category C3 (IEC61643-21) - Line/Line)	Up	40 V
Line resistance		< 4.7 Ohm
Mechanical Characteristics		
Technology		GDT+Clamping diode
SPD configuration		1-pair+shielded
Connection to Network		By screw terminal: cross section 0.5-2.5mm²
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Protection rating		IP20
Failsafe mode		Short-circuit
Spare module(s)		DLAM-24D3
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A
Part number		
6403011		

