

Retrofit inverter for optimised solar energy back-up

- ✓ Optimised energy autonomy
- ✓ Smart and efficient operations
- ✓ Modern and compact design
- ✓ Highest safety standards

Ideal for solar power system upgrades and retrofit projects, the SBP G2 battery inverter is installed on the AC-side of the on-grid inverter and can be combined with a range of battery capacities, including GoodWe low-voltage battery series Lynx Home U. By facilitating maximum back-up of generated solar energy, house owners can achieve a high degree of autonomy.

 UPS level switching <10ms

 Wide battery voltage range

 Parallel connection



Technical Data		GW3600-SBP-20	GW5000-SBP-20	GW6000-SBP-20
Battery Input Data				
Battery Type ^{*1}		Li-Ion		
Nominal Battery Voltage (V)		48		
Battery Voltage Range (V)		40 ~ 60		
Max. Continuous Charging Current (A) ^{*1}		75	120	120
Max. Continuous Discharging Current (A) ^{*1}		75	120	120
Max. Charging Power (W) ^{*1}		3600	5000	6000
Max. Discharging Power (W)		3900	5300	6300
AC Output Data (On-grid)				
Nominal Apparent Power Output to Utility Grid (VA)		3680	5000 ^{*2}	6000 ^{*2}
Max. Apparent Power Output to Utility Grid (VA)		3680	5000 ^{*2}	6000 ^{*2}
Max. Apparent Power from Utility Grid (VA)		7360	10000	10000
Nominal Output Voltage (V)		220 / 230 / 240		
Nominal AC Grid Frequency (Hz)		50 / 60		
Max. AC Current Output to Utility Grid (A)		16.7	22.7	27.3
Max. AC Current From Utility Grid (A)		33.5	43.5	43.5
Power Factor		~ 1 (Adjustable from 0.8 leading to 0.8 lagging)		
Max. Total Harmonic Distortion		<3%		
AC Output Data (Back-up)				
Back-up Nominal Apparent Power (VA)		3680	5000	6000
Max. Output Apparent Power (VA)		3680 (7360@10sec)	5000 (10000@10sec)	6000 (10000@10sec)
Max. Output Current (A)		16.7	22.7	27.3
Nominal Output Voltage (V)		220 / 230 / 240		
Nominal Output Frequency (Hz)		50 / 60		
Output THDv (@Linear Load)		<3%		
Efficiency				
Max. Battery to AC Efficiency		95.5%		
Protection				
Residual Current Monitoring		Integrated		
Anti-islanding Protection		Integrated		
AC Overcurrent Protection		Integrated		
AC Short Circuit Protection		Integrated		
AC Overvoltage Protection		Integrated		
AC Surge Protection		Type III		
Remote Shutdown		Integrated		
General Data				
Operating Temperature Range (°C)		-25 ~ +60		
Relative Humidity		0 ~ 95%		
Max. Operating Altitude (m)		3000 (>2000 derating)		
Cooling Method		Natural Convection		
User Interface		LED, WLAN + APP		
Communication with BMS		CAN		
Communication with Meter		RS485		
Communication with Portal		WiFi / WiFi + LAN / 4G		
Weight (kg)		19.2	19.5	19.5
Dimension (W × H × D mm)		505.9 × 434.9 × 154.8		
Topology		Isolated		
Self-consumption at Night (W)		<10		
Ingress Protection Rating		IP65		
Mounting Method		Wall Mounted		

¹: The actual charge and discharge current/power also depends on the battery.

²: 4600 for VDE-AR-N4105 & NRS 097-2-1.

*: Please visit GoodWe website for the latest certificates.